

### Product type designation

Product description

**PROFIBUS bus connector, RS485, screw, without PG socket, 90°**  
 PROFIBUS bus connector, RS485, screw, without PG socket, 90°  
 SIMATIC DP, BUS CONNECTOR FOR PROFIBUS UP TO 12  
 MBIT/S 90 DEGREE ANGLE OUTGOING CABLE, 15,8 X 64 X 35,6  
 MM (WXHXD), TERMINAT. RESIST. WITH ISOLAT. FUNCTION,  
 WITHOUT PG SOCKET



Suitability for use

For connecting PROFIBUS nodes to the PROFIBUS bus cable

### Transmission rate

Transfer rate / with PROFIBUS DP

9.6 kbit/s ... 12 Mbit/s

### Interfaces

Number of electrical connections

- for PROFIBUS cables
- for network components or terminal equipment

2

1

Type of electrical connection

- for PROFIBUS cables

Screw

### Mechanical data

Design of terminating resistor

Integrated resistor combination that can be selected with slide switch

Material / of the enclosure

plastic

### Design, dimensions and weight

Width

15.8 mm

Height

64 mm

Depth

35.6 mm

Net weight

10 g

### Permitted ambient conditions

Ambient temperature

- during storage
- during transport

-40 ... +70 °C

-40 ... +70 °C

Protection class IP	IP20
<b>Product properties, functions, components / general</b>	
Product property	
• silicon-free	Yes
Product component	
• PG connection socket	No
• strain relief	Yes
<b>Standards, specifications, approvals</b>	
Certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
<b>last modified:</b>	16.04.2015